





Gebrauchsanweisung
52 3257

Montageanleitung
52 1893

Beistellsatz
26 4862

Temp.-Regler
Rep.-Satz
26 5271



	V01	V02	V03
Pos.	Aspera EMT 40 CLP	Danfoss TLY7KK2	Matsushita ESS 60E
1	14 1839	14 2059	14 2158
2			
3	17 1315	15 1055	18 3589
4			
5	17 0882	15 0760	18 3590
6	17 0881	15 1072	18 3591
7	16 9319	16 9319	16 9319
8	26 4879	26 4879	26 4879
9	05 0166	05 0166	05 0166
10		16 5852	
11			
12			

TECHNISCHE DATEN / TECHNICAL DATA / DONNEES TECHNIQUES				
Verdichter/Compressor/Compresseur		Aspera	Danfoss	Matsushita
Typ/Type		EMT 40 CLP	TLY7KK2	ESS 60E
Förderleistung/Delivery/Débit		l/h	1168	1076
Anlaufstrom/Starting current/Cour de démarrage		A	5,7	5,6
Widerstand/Resistance/Résistance Ha/main/prin		W	27,1	30,6
Hi/aux		W	27,2	26,7
Temp.-Regler/Thermostat		KER		
Typ/Type		RCO		
Regelstellung/Position		kalt	warm	
Schaltwerte/Switching values		ein"	-23,0	-15,0
Valeurs de commutation		aus"	-31,0	-21,0
Füllmenge/Fill.quantity/Charge		R600a	*	
Anschlußwert/Conn.load/Puiss. connectée		W	88	71
Heizung/Heater/Chauffage				
Widerstand/Resistance/Résistance		W		
Leistung/Power/Puissance		W		
Ventilator/Blower/Ventilateur				
Widerstand/Resistance/Résistance		W		
Temp.-Regler/Thermostat				
Magnetventil/Magnetic valve/Electrovanne				
Widerstand/Resistance/Résistance		W		
Spannung/Voltage/Tension		V		

* siehe Typenschild